



600 Series Patio Doors






The 600 series patio doors are the result of 35 years of experience at Novatech. Beyond their **sleek contempory style**, these doors feature a unique and **innovative wood insert in the jambs** for added strength and easy installation, a **broad host of options** to suit any type of construction and a design that offers **superior energy efficiency**.



Enjoy the View With the **630** Patio Door

The 630 patio door matches any architectural style. Its **narrow sash** and **large glass surface** let you make the most of the outside view.



The **Imagine** Patio Door — Elegant and Stylish

Imagine provides all the charm of a **garden door** without the drawbacks of a hinged door. Its **wide sash** and styling options let you customize your door to be the focal point of the room — both architectural and practical.







Wood reinforcements in the jamb

Unique to the 600 series, a pine insert in the PVC jambs provide additional strength and a sturdy wood backing for easy installation.

| Features | 630 | IMAGINE | | |
|---|--------|---------|--|--|
| Frame | | | | |
| Multi-chambered PVC frame with wood inserts in side jambs | ✓ | × | | |
| Frame depths from 5 ¾" to 11 ¾" | ✓ | ✓ ✓ | | |
| Quick draining sill sloped at 9° | ✓ | | | |
| Aluminum sill cover Improved sill durability and superior finish | Option | < | | |
| PVC cavity filler cap | Option | ✓ | | |
| Sash | | | | |
| Steel reinforcements in the vertical stiles | ✓ | ✓ | | |
| 45° fusion welded corners and interior glazing stops | | ✓ | | |
| Wide garden door style sash | | ✓ | | |
| Insulated Glass | | | | |
| Tempered Low E glass with low-conductive spacer | × | × | | |
| Hardware | | | | |
| 9600 mortise handle NEW | ✓ | | | |
| Look contemporary style mortise handle NEW | | ✓ | | |
| View contemporary style mortise handle NEW | | Option | | |

Options





Colors



More than 100 colours available. Custom colours on demand.



| Performance | | 630 | IMAGINE | | |
|--|--|--|---|--|--|
| Water penetrati Uniform load st Global | Air leakage resistance | A3 | A3 400 Pa DP-45 PG-R45 | | |
| | Water penetration resistance | 330 Pa — 400 Pa with Sill Tower Riser (Option) | | | |
| | Uniform load structural test Global | DP-45 | | | |
| | | PG-R45 | | | |
| | Laboratory tested | Reference 71½" × 81" door Harmonized standards — AAMA /WDMA / CSA101 / I.S.2 / A440-11 | Reference 71½" × 81" door Harmonized standards — AAMA / WDMA / CSA101 / I.S.2 / A440-11 | | |

630

IMAGINE

| Insulated Glass | | ER | U Value | | ER | U Value | U Value | |
|------------------|------------------------|----|---------|-------------|----|---------|-------------|--|
| Standard Double- | pane — Low E on face 3 | 35 | 1.70 | ENERGY STAR | 31 | 1.70 | | |
| Option Triple-p | ane — Low E on face 5 | _ | _ | | 35 | 1.42 | ENERGY STAR | |

Warranty



20-year limited warranty. See the detailed warranty on our website.

The information in this brochure is current as of the date of publication but is subject to change.

Novatech^{*}